



**MELFAS Inc.**

## **BioPoint™ MMS-458® Datasheet**

Capacitive Touch Screen Sensor IC

---

### Feature Overview

- **High Performance Capacitance sensing**
  - 32-bit ARM Cortex™ M0+ Processor
  - Embedded DSP for Multi-touch Processing
  - Support up to 8.4 inch diagonal ( 5mm sensor pitch )
  - Provide High-Quality Accuracy and Linearity performance on 780 nodes ( 20×38 electrodes )
  - Provide effective 7.2-V TX drive for enhancing SNR Performance
  - TX Driving Frequency up to 700 kHz
  - 10 Fingers Multi touch report rate : Typical 100Hz ( Single touch up to 240Hz ) depending on the active current and the noise environment
  - Small finger support down to 4mm
  - Support to 1.5mm Passive Stylus contact
  - Support to thickness glove touch input (Test condition : 10Φ conducted rod @ 3T Acryl)
- **Low power consumption and I/O modes**
  - 2.4V to 3.6V Single supply voltage
  - Active current : 8.0mA ( Typical )
  - Sleep current : Max 1uA
  - Support 13-type wake-up gesture scheme on Low power mode ( Max 0.5mA )
  - Available for Open-drain/Push pull mode on I/O pins
  - Available for CE pin as wake up function
- **Communication interface**
  - I<sup>2</sup>C-compatible for Standard ( 100kbps ) / Fast ( 400kbps ) mode as Slave
- **48kbytes E-FLASH and 14kBytes SRAM**
  - ISC by serial interface, F/W can be updated in systems
- **Robust to the noisy environment**
  - Common mode noise immunity > 20 Vpp
  - Immune to the Charger noise
- **Package**
  - BGA 81balls 5×5×0.6T, 0.50mm ball pitch

Datasheet (REV. 1.0)

Information furnished by MELFAS is believed to be accurate and reliable. However, no responsibility is assumed by MELFAS for its use, nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of MELFAS.

World Wide Web Site: <http://www.melfas.com/english/index.asp>

Revised APR, 01, 2015